



## Stone Router 1325/ 1530



# Machine parts

			
<p>Oil system Convenient to lubricate machine, long lifespan</p>	<p>Leadshine stepper motor</p>	<p>DSP controller</p>	<p>Aluminum bed with PVC</p>
			
<p>BEST inverter</p>	<p>HQD air cooled spindle</p>	<p>High quality TBI ball screw</p>	<p>Double bags dust collector</p>
			
<p>High accuracy slider</p>	<p>High soft shielding wire Small interference with inverter</p>	<p>Popular Omron limit switch</p>	<p>Level test to test the precision when building</p>

## Product Features

1. Entire Mild Steel Frame Structure, high temperature to make the frame regain the same steel feature of high strength, ensure the bed undeformable.
2. Gantry movement style structure, scientific and reasonable table design. Optional automatic oil lubrication system, Foamable D-deformable.
3. The X-axis and Y-axis are transmitted by the imported gear and rack with high precision. Running more stable and quiet with high speed and great power.
4. The Z-axis is driven by the ball bearing screw rod with original screw nut of European brand. Its travel is up to 200mm.
5. The large-scale straight-liner square guiding track is imported from Taiwan with high steel feature.
6. Maintenance free for 1 year

## Samples



Model	1325 & 1530
Working Area (X*Y*Z)	1300mm* 2500mm, 1500mm*3000mm
Working Table	Aluminum Profile Working Table with T-Slot PVC Plate, vacuum bed
Spindle	3.5, 4.5, 6KW Air/Water-Cooling Spindle
Control System	DSP Rich Auto A 11, NK105
Resolution	+ _ 0.05 mm
Spindle Speed	18000-24000 rpm
Tool Diameter	3.175 mm, 6.0mm , 12.7mm
Working Voltage	AC220v/50hz, 380v
Engraving Speed	12000mm / min
Feeding Height	220mm
Working Dictate	HPGL , G Code